

# ThermaLite™ Thermometers

with assured accuracy for life

- ✓ range -39.9 to 149.9 °C, with a ±0.5 °C accuracy
- ✓ water resistant IP65 when used with silicone boot
- ✓ ThermaLite 2 includes CalCheck function
- ✓ FREE traceable certificate of calibration

NEW!

The ThermaLite digital thermometers display temperature over the range of -39.9 to 149.9 °C with a 0.1 °C resolution and an accuracy of ±0.5 °C. This accuracy is guaranteed for life, due to the instruments advanced electronics. The ThermaLite 2 incorporates a CalCheck, °C/°F and hold functions.

The thermometers weigh only 45 grams, including battery and feature a clear, easy to read LCD display with an open circuit 'Err' and low battery indication. The ThermaLite's auto-power off facility turns the instrument off automatically after 10 minutes, maximising battery life. The thermometer is housed in a high impact ABS plastic case which includes the Biomaster additive that reduces bacterial growth, ideal for routine day-to-day food and catering applications.

The pointed, Ø3.3 x 130 mm stainless steel, penetration probe is ideal for measuring the temperature of food and semi-solid materials. The ThermaLite is available in six colours, suitable for different applications.

### ThermaLite 2 with CalCheck function

The ThermaLite 2 incorporates a CalCheck 0 °C function. The CalCheck can be activated by pressing both the 'on/off' and 'hold' buttons simultaneously at the time of switching the unit on.



The ThermaLite is waterproof to IP65 when used in conjunction with the 830-280 protective silicone boot

| order code | description              |
|------------|--------------------------|
| 226-301    | ThermaLite 1 - grey      |
| 226-311    | ThermaLite 1 - white     |
| 226-321    | ThermaLite 1 - yellow    |
| 226-331    | ThermaLite 1 - green     |
| 226-341    | ThermaLite 1 - red       |
| 226-351    | ThermaLite 1 - blue      |
| 226-302    | ThermaLite 2 - grey      |
| 226-312    | ThermaLite 2 - white     |
| 226-322    | ThermaLite 2 - yellow    |
| 226-332    | ThermaLite 2 - green     |
| 226-342    | ThermaLite 2 - red       |
| 226-352    | ThermaLite 2 - blue      |
| 830-280    | protective silicone boot |



| specification | ThermaLite 1 & 2                |
|---------------|---------------------------------|
| range         | -39.9 to 149.9 °C               |
| resolution    | 0.1 °C/°F                       |
| accuracy      | ±0.5 °C (-39.9 to 124.9 °C)     |
| battery       | 3 volt CR2032 lithium coin cell |
| battery life  | 3000 hours                      |
| sensor type   | thermistor                      |
| display       | 10 mm LCD                       |
| dimensions    | Ø29 x 246 mm                    |
| weight        | 45 grams                        |

FREE traceable certificate of calibration included

